

## H22/23 Installation into 96-00 Civic

Thank you for purchasing the Hasport EKH1 bolt in mount kit. This instruction sheet covers the installation of the H22, H23 or F22 engines into the 96-00 Civic. This only deals with the installation of the engine, there are several other consideration also when installing this engine such as shift linkage and wiring. That information is not in this document.

**Right Hand Mount**



**Right Hand Bracket**



**Rear Mount**



**Left Mount Bracket**



**Left Mount**



**Hardware**

Quantity	Description
1	10 mm X 1.25 X 30
1	10 mm X 1.25 X 45
1	10 mm X 1.25 X 50
3	10 mm Flat Washers
2	12 mm Flat Washers
1	12 mm X 1.25 X 110
1	12 mm X 1.25 Nylon Nut

**Hardware**

Quantity	Description
1	12 mm Flat Washer
1	½" Thick AN Washer

**Hardware**

Quantity	Description
2	10 mm X 1.25 X 30
1	10 mm X 1.25 X 40
3	10 mm Flat Washer

**Hardware**

Quantity	Description
2	12 mm X 1.25 X 40
4	12 mm Flat Washers
1	12 mm X 1.25 X 110
1	12 mm X 1.25 Nylon Nut

Engine bay preparation:

Installing the engine the rear bracket for the H22 needs to come from a 92 up Prelude (part number 50827-SS0-010). Whether you install the engine from the top or the bottom, install the rear bracket as the motor is being moved into place. Insert only the top bolt and rear mount bolt on the rear bracket at this time. Install the left-hand mount at this time. Lower the transmission side slightly below the frame rail and install the transmission bracket at this time if you haven't already. Now raise transmission into place.

Hasport Products that may be helpful with your installation:  
 EGHAXCMP – Compete axles. No need to build your own.  
 EGHRB – Rear Bracket.